E I DUPONT DE NEMOURS & CO INC ENGINEERING POLYMERS, CHESTNUT RUN PLAZA, PO BOX 80713, WILMINGTON DE 19880-0713



Zytel: 70G25HSLR

Polyamide 66 (PA66), pellets, glass reinforced

1.5 mm, ALL HB75 IEC 60695-11-10, -2 电气性能 但 测试方法 熱丝引燃 (HWI) UL 746 1.5 mm 1.5 mm PLC 4 3.0 mm 第电弧燃烧指数(HAI) UL 746 1.5 mm 1.5 mm PLC 0 3.0 mm 小电强度 24 kV/mm ASTM D149 IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D257 Kth 值 测试方法 RTI Elec UL 746 0.71 mm 105 °C 1.5 mm 120 °C RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C 3.0 mm 95.0 °C 3.0 mm 95.0 °C 3.0 mm 105 °C 3.0 mm 105 °C 3.0 mm 95.0 °C 3.0 mm 95.0 °C 3.0 mm 105 °C 3.0 mm 105 °C 3.0 mm 105 °C 3.0 mm 105 °C 3.0 mm	可燃性		测试方法
3.0 mm, ALL HB UL 94 3.0 mm, ALL HB40 IEC 60695-11-10, -2 1.5 mm, ALL HB75 IEC 60695-11-10, -2 4 C4LB 1 1 1 熟설引燃 (HWI) UL 746 UL 746 1.5 mm PLC 4 UL 746 1.5 mm PLC 2 Image: Comparison of the state of	UL 阻燃等级		
3.0 mm, ALL HB40 IEC 60695-11-10, -2 1.5 mm, ALL HB75 IEC 60695-11-10, -2 24C性能 ////////////////////////////////////	1.5 mm, ALL	HB	UL 94
1.5 mm, ALL HB75 IEC 60695-11-10, -2 电气性能 値 測试方法 熱丝引燃 (HWI) UL 746 1.5 mm 1.5 mm PLC 4 3.0 mm 3.0 mm PLC 2 高电弧燃烧指数(HAI) UL 746 1.5 mm PLC 0 0.0 mm 1.5 mm 3.0 mm PLC 0 0.0 mm 0.0 mm 介电强度 24 kV/mm ASTM D149 IEC 60243-1 1.0 E+13 ohms·cm ASTM D257 IEC 60093 耐电压电型起痕速率 (HVTR) PLC 0 UL 746 4STM D257 IEC 60093 ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 ASTM D495 4.0 MM A95 大性能 値 测试方法 1.0 E+13 ohms·cm IEC 60093 耐电弧性 PLC 5 ASTM D495 4.0 M A95 大性能 値 测试方法 1.0 E*13 ohms·cm IEC 60093 耐电弧性 PLC 5 O.71 mm 1.0 C 1.0 E*1 0.71 mm 105 °C 1.0 T46 1.5 mm 1.5 mm 95.0 °C 0.0 m 0.0 m 1.5 mm 95.0 °C 0.0 m 0.0 T46 1.5 mm 95.0 °C 0.0	3.0 mm, ALL	HB	UL 94
电气性能 值 测试方法 热丝引燃 (HWI) UL 746 1.5 mm 1.5 mm PLC 4 3.0 mm PLC 2 高电弧燃烧指数(HAI) UL 746 1.5 mm 0.1 T46 1.5 mm PLC 0 0.1 T46 1.5 mm 3.0 mm PLC 0 0.1 T46 1.5 mm 3.0 mm PLC 0 0.1 T46 1.5 mm 小电强度 24 kV/mm IEC 60243-1 IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 0.1 T46 4 ASTM D149 体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 ASTM D495 X性能 值 测试方法 105 °C RTI Elec UL 746 1.20 °C UL 746 1.5 mm 120 °C 120 °C RTI RTI Imp UL 746 UL 746 1.5 mm 1.5 mm 95.0 °C 3.0 mm 95.0 °C 3.0 mm 95.0 °C 3.0 mm 105 °C	3.0 mm, ALL	HB40	IEC 60695-11-10, -20
熱丝引燃 (HWI) UL 746 1.5 mm PLC 4 3.0 mm PLC 2 高电弧燃烧指数(HAI) UL 746 1.5 mm PLC 0 3.0 mm PLC 0 3.0 mm PLC 0 分电强度 24 kV/mm ASTM D149 IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 X性能 0 JUC 746 0.71 mm 105 °C UL 746 1.5 mm 120 °C 3.0 mm 3.0 mm 95.0 °C UL 746 1.5 mm 95.0 °C UL 746	1.5 mm, ALL	HB75	IEC 60695-11-10, -20
1.5 mm PLC 4 3.0 mm PLC 2 高电弧燃烧指数(HAI) UL 746 1.5 mm PLC 0 3.0 mm PLC 0 分电强度 24 kV/mm ASTM D149 IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm IEC 60093 IEC 60093 耐电弧性 PLC 5 ASTM D495 热性能 位 测试方法 RTI Elec UL 746 UL 746 0.71 mm 105 °C 120 °C 3.0 mm 120 °C UL 746 1.5 mm 95.0 °C UL 746 1.5 mm 105 °C UL 746 1.5 mm 105 °C UL 746	电气性能	值。	测试方法
3.0 mm PLC 2 高电弧燃烧指数(HAI) UL 746 1.5 mm PLC 0 3.0 mm PLC 0 分电强度 24 kV/mm ASTM D149 IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 X性能 值 测试方法 RTI Elec UL 746 UL 746 0.71 mm 105 °C UL 746 1.5 mm 120 °C UL 746 1.5 mm 95.0 °C UL 746 1.5 mm 0.0 mm 05.0 °C 3.0 mm 105 °C UL 746	热丝引燃 (HWI)		UL 746
高电弧燃烧指数(HAI) UL 746 1.5 mm PLC 0 3.0 mm PLC 0 介电强度 24 kV/mm ASTM D149 IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 X性能 值 测试方法 RTI Elec UL 746 0.71 mm 105 °C 1.5 mm 120 °C 3.0 mm 95.0 °C RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746	1.5 mm	PLC 4	
1.5 mm PLC 0 3.0 mm PLC 0 介电强度 24 kV/mm ASTM D149 IEC 60243-1 富电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm IEC 60093 耐电弧性 PLC 5 ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 Xeft 值 Nitfs X NTI Elec UL 746 UL 746 0.71 mm 105 °C UL 746 1.5 mm 120 °C UL 746 3.0 mm 120 °C UL 746 1.5 mm 95.0 °C UL 746 1.5 mm 95.0 °C UL 746 1.5 mm 105 °C UL 746 1.5 mm 105 °C UL 746	3.0 mm	PLC 2	
3.0 mm PLC 0 介电强度 24 kV/mm ASTM D149 IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 X性能 値 测试方法 RTI Elec UL 746 UL 746 0.71 mm 105 °C UL 746 1.5 mm 120 °C UL 746 1.5 mm 95.0 °C UL 746 1.5 mm 105 °C UL 746 1.5 mm 105 °C UL 746	高电弧燃烧指数(HAI)		UL 746
介电强度 24 kV/mm ASTM D149 IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 <u>X性能 値 测试方法 RTI Elec UL 746 UL 746 0.71 mm 105 °C 120 °C 1.5 mm 120 °C UL 746 1.5 mm 95.0 °C UL 746 1.5 mm 95.0 °C UL 746 1.5 mm 95.0 °C UL 746 1.5 mm 105 °C UL 746 1.5 mm 105 °C UL 746 </u>	1.5 mm	PLC 0	
プモ強度 24 kV/mm IEC 60243-1 高电压电弧起痕速率 (HVTR) PLC 0 UL 746 体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 热性能 値 测试方法 RTI Elec UL 746 0.71 mm 105 °C 1.5 mm 120 °C 3.0 mm 95.0 °C 3.0 mm 95.0 °C 3.0 mm 105 °C 1.5 mm 95.0 °C 3.0 mm 105 °C 3.0 mm 105 °C 3.0 mm 105 °C	3.0 mm	PLC 0	
体积电阻率 1.0E+13 ohms·cm ASTM D257 IEC 60093 耐电弧性 PLC 5 ASTM D495 熱性能 值 测试方法 RTI Elec UL 746 UL 746 0.71 mm 105 °C 1.5 mm 1.5 mm 120 °C UL 746 1.5 mm 95.0 °C 1.5 mm 1.5 mm 95.0 °C 1.5 mm 1.5 mm 95.0 °C 1.5 mm 3.0 mm 95.0 °C 1.5 mm 1.5 mm 95.0 °C 1.5 mm 3.0 mm 95.0 °C 1.5 mm 3.0 mm 105 °C 1.5 mm 3.0 mm 105 °C 1.5 mm 3.0 mm 105 °C 1.5 mm	介电强度	24 kV/mm	
体候电阻单 1.0E+13 ohms*cm IEC 60093 耐电弧性 PLC 5 ASTM D495 蒸性能 值 测试方法 RTI Elec UL 746 0.71 mm 105 °C 1.5 mm 120 °C 3.0 mm 120 °C RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C 3.0 mm 105 °C 3.0 mm UL 746 1.5 mm 95.0 °C 3.0 mm 105 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 105 °C 3.0 mm 105 °C 3.0 mm 105 °C	高电压电弧起痕速率 (HVTR)	PLC 0	UL 746
热性能 值 测试方法 RTI Elec UL 746 0.71 mm 105 °C 1.5 mm 120 °C 3.0 mm 120 °C RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 105 °C 3.0 mm 105 °C 3.0 mm 110 °C	体积电阻率	1.0E+13 ohms·cm	
RTI Elec UL 746 0.71 mm 105 °C 1.5 mm 120 °C 3.0 mm 120 °C RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI 95.0 °C RTI UL 746 1.5 mm 95.0 °C 3.0 mm 105 °C 3.0 mm 105 °C 3.0 mm 110 °C	耐电弧性	PLC 5	ASTM D495
0.71 mm 105 °C 1.5 mm 120 °C 3.0 mm 120 °C RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI 95.0 °C RTI UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 105 °C 3.0 mm 110 °C	热性能	值。	测试方法
1.5 mm 120 °C 3.0 mm 120 °C RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 010 °C RTI UL 746 1.5 mm 105 °C 3.0 mm 110 °C	RTI Elec		UL 746
3.0 mm 120 °C RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 105 °C 3.0 mm 105 °C 3.0 mm 110 °C	0.71 mm	105 °C	
RTI Imp UL 746 1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 105 °C 3.0 mm 110 °C	1.5 mm	120 °C	
1.5 mm 95.0 °C 3.0 mm 95.0 °C RTI UL 746 1.5 mm 105 °C 3.0 mm 110 °C	3.0 mm	120 °C	
3.0 mm 95.0 °C RTI UL 746 1.5 mm 105 °C 3.0 mm 110 °C	RTI Imp		UL 746
RTI UL 746 1.5 mm 105 °C 3.0 mm 110 °C	1.5 mm	95.0 °C	
1.5 mm 105 °C 3.0 mm 110 °C	3.0 mm	95.0 °C	
3.0 mm 110 °C	RTI		UL 746
	1.5 mm		
物理性能		110 °C	
	物理性能	值。如此	测试方法
Dimensional Stability 0.0 % ASTM D1042 ISO 2796	Dimensional Stability	0.0 %	



Notice of Disclaimer

By accessing this Yellow Card data information sheet and the database from which this information was generated (the "Yellow Card"), the user acknowledges and accepts the terms and conditions upon which this Yellow Card is made available. This Yellow Card, the database from which it was generated, and all related materials, support, and services, are made available by UL for use only by permission and "as is", without any representation or warranty of any kind, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose or that the products identified in this Yellow Card will satisfy the user's requirements. UL cannot and does not warrant that the data contained in this Yellow Card is current, accurate, or complete. The user must independently confirm the conformance of any product to the applicable standards or requirements with the manufacturer of that product. Permission to access this Yellow Card may be withdrawn at any time by UL in its sole discretion. The identification of products and companies on this Yellow Card does not in any way imply endorsement of those products or companies by UL. UL does not assume and expressly disclaims, liability to any person for any loss or damage (including lost profits, lost savings, or any indirect, special, incidental, consequential or punitive damages whether or not UL has been advised of the possibility of such damages) arising out of, or in connection with, the use of this Yellow Card regardless of the cause or causes of such loss or damage.